



## Specifications: D 125-32 Diesel Pile Hammer

### Dimensions approx:

Hammer Length:	A1	7800 mm	25' 7" ft
Hammer Length w/starter guides:	A	8865 mm	29' 1" ft
Outer diameter of impact block:	B	910 mm	3' ft
Min. Guiding Width:	C	1219 mm	42" in
Width of Hammer:	D	1030 mm	41" in
Hammer Center to Pump Guard:	F	560 mm	1' 10" ft
Hammer Center to Trip:	G	370 mm	1' 3" ft
Hammer Depth:	H	1220 mm	4' ft

Pump Setting 1	251 kNm	184,538 ft.lbs.
Pump Setting 2	314.2 kNm	231,020 ft.lbs.
Pump Setting 3	347.7 kNm	255,660 ft.lbs.
Pump Setting 4	418.2 kNm	307,563 ft.lbs.

### Weights approx:

Weight of diesel pile hammer approx.:	30.81 <b>US tons</b>	61,613 lbs
Weight of piston approx.:	12,500 kg	27,557.8 lbs
Impact Block approx.:	3040 kg	6,702 lbs
Tripping device approx.:	870 kg	1,918 lbs
Tool box approx.:	125 kg	275.6 lbs

### Energy Per Blow

Max:	418.2 kNm	307,563 ft lbf
Min:	251 kNm	184,538 ft lbf
Number of blows:	36–45 min	

### Batter Info

Max. gradient of batter pile driven: 1:2

### Consumption

Diesel fuel:	36 L hr.	9.5 gph
Lubrication oil:	3.6 L hr.	1 gph

### Volume

Diesel oil tank:	190 L	50.2 gal
Lube tank:	60 L	15.9 gal

